



# MZÖL DEZO 77

## SAE 20W50 API CF-4/SJ

### Product Description

**MZÖL DEZO 77** is a heavy duty Diesel Engine Oil that meets API: CF-4/SJ SAE: 20W50 classification. Formulated for turbo-charged and non-turbo charged engines in normal conditions.

### APPLICATIONS

This oil is recommended for use in turbo-charged and non-turbo charged diesel engines of mixed fleet, heavy earth moving equipments and generator sets operating over wide range of temperatures throughout the year.

### FEATURES & BENEFITS

- High resistant to oxidation, oil degradation and oil thickening.
- High performance in keeping the engine clean.
- Maintains engine's power and efficiency.
- Lowers servicing costs.
- Enables efficient control of soot, sludge and piston deposits.
- Controls engine wear.
- Extended engine's life.
- Recommended to use in Mixed Fleet of Diesel Engines, Heavy Earth Moving Equipments and Gen Sets.

### SPECIFICATIONS

SAE	20W50
API	CF-4/SJ
Approved Vehicle Brands	Furnished upon request

### TYPICAL CHARACTERISTICS

Test	Unit	Average Results
Appearance		Clear
Color		3.0
Density at 85°F	g/ml	0.8851
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	Report
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	19.50
Viscosity index		128

Total Base number	Mg KOH/g	9.00
Flash point	°C	240
App. Viscosity CCS at -15°C	mPa.s	8250
Copper Corrosion		Pass
Demulsibility at 82°C		Pass
Water (Crackle)		-ve

We reserve right to alter the general characteristics of our products to let our customers benefit of the latest technical evolution.